

CaterRent

Food Service Equipment Rental & Sales

260 North 24th Avenue, Minneapolis, MN 55411-2236

Phone: 612-588-1188 Technician: 612-436-1499

Tools Needed for Operation: Crescent Wrench & Soapy Water

General Operating Instructions for *Propane* Equipment:

1. Ensure that the equipment is turned off and the *propane* supply valve is **CLOSED** before connecting the fuel tank.
2. Tighten connections with a **crescent wrench** until tight (FULL Stop).
 - Tightening with your fingers will not get it tight enough.
3. Ensure that hoses are not kinked and are not near any burners or other areas that will become hot during use.
4. Keep *propane* at least 10 feet away from the equipment.
5. Turn *propane* gas on and apply soapy water on connections at equipment, *propane* tank, and regulator. If any bubbles appear, connections are leaking. Tighten fittings tighter and reapply soapy water. If no bubbles appear, proceed with lighting.
6. When the equipment is not in use, close *propane* supply valves.
7. Before replacing a *propane* tank, close the supply valve and turn the equipment off.
8. If you smell gas, hear a hissing sound, or see a white or icy substance near any connections, immediately close the *propane* supply valve, turn the equipment off, and remove any other ignition source.
9. Do not store spare *propane* tanks near the equipment.

If you have a leak, turn off all nearby sources of flame.